R&D Batteries, Inc.

1986

Specifications

Nominal Voltage	12V
Rated Capacity (20-hour rate)	9Ah
Dimensions	
Length	151±1.5mm (5.94inch)
Width	65±1mm (2.56inch)
Height	94±1mm (3.70inch)
Total Height	100±1mm (3.94inch)
Approximate Weight	2.65kg (5.84lbs)±4%

Outer Dimensions



Terminal Type



Characteristics

Capacity (25°C)	
20HR (10.5V)	9Ah
10HR (10.5V)	8.4Ah
1HR (9.60V)	5.4Ah
Terminal Type	F1
Internal Resistance	Approx. 19m Ω
Capacity affected by temperature (20HR)	
40°C	102%
25°C	100%
0°C	85%
-15°C	65%
Self-Discharge (25°C)	
3 months	Remaining Capacity: 91%
6 months	Remaining Capacity: 82%
12 months	Remaining Capacity: 65%
Nominal operating temperature	25°C±3°C (77°F±5°F)
Operating Temperature range	
Discharge	-15°C~50°C (5°F~122°F)
Charge	-10°C~50°C (14°F~122°F)
Storage	-20°C~50°C (-4°F~122°F)
Float charging voltage (25°C)	13.50 to 13.80V Temperature compensation: -18mV/°C
Cyclic charging voltage (25°C)	14.50 to15.00 V Temperature compensation: -30mV/°C
Maximum charging current	2.7A
Maximum discharge current	135A (5 sec.)
Designed Floating Life (20°C)	5 years

Construction

Component	Positive Plate	Negative Plate	Container	Cover	Separator	Electrolyte	Safety Valve	Terminal
Raw Material	Lead Dioxide	Lead	ABS	ABS	AGM	Sulfuric Acid	Rubber	Copper

Constant Current Discharge Characteristics

F.V/Time	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	34.4	21.8	17.0	9.59	5.90	3.22	2.23	1.85	1.57	0.85	0.46
9.90V	33.3	21.1	16.6	9.39	5.81	3.21	2.22	1.83	1.56	0.85	0.45
10.2V	32.0	20.3	16.0	9.11	5.66	3.18	2.20	1.82	1.55	0.84	0.45
10.5V	30.6	19.4	15.4	8.89	5.55	3.13	2.19	1.81	1.54	0.84	0.45
10.8V	28.9	18.3	14.6	8.56	5.38	3.05	2.12	1.75	1.49	0.82	0.44

Constant Power Discharge Characteristics

F.V/Time	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	384	246	194	110	68.3	37.7	26.5	22.0	18.7	10.2	5.48
9.90V	372	238	189	108	67.2	37.5	26.3	21.8	18.6	10.2	5.46
10.2V	357	228	182	104	65.5	37.2	26.2	21.7	18.5	10.1	5.43
10.5V	341	219	176	102	64.2	36.6	26.0	21.5	18.4	10.1	5.40
10.8V	322	206	167	98.1	62.3	35.7	25.2	20.9	17.8	9.87	5.29

*Note: The above characteristics data can be obtained within three charge or discharge cycles.

R&D Batteries, Inc.

1986

Discharge Characteristics



Charging Characteristics



Effect of Temperature on Capacity



Self-discharge Characteristics



Floating Life on Temperature



Cycle Life on D.O.D



Relationship for OCV and Capacity



Relationship for Charging voltage and Temperature



R&D Batteries Inc.

3300 Corporate Center Drive
Burnsville, MN 55306 1 (800) 950-1945
www.rdbatteries.com
info@rdbatteries.com

Quality Management ISO 13485 DEKRA certified